

# INVENGO XC-AF12 HIGH PERFORMANCE





# About Invengo's XC-AF12 High Performance Antenna

Invengo XC-AF12 antenna offers high gain, ruggedness and excellent shock and vibration resistance in a unique design. The XC-AF12 circular polarized antenna is ideal for transportation, logistics, warehousing and asset tracking applications.



Invengo – the global RFID technology provider – is a leading developer and manufacturer of high quality, intelligent RAIN RFID (UHF) and NFC (HF) inlays, tags and connectivity solutions utilized in the Internet of Things (IoT). With a focus on RFID innovation, Invengo has created a leading product line in retail, library, pharmaceutical, healthcare, (public) transportation and many other industries.

Invengo Technology Pte. Ltd. (SG) is the International Headquarters of Invengo Information Technology Co. Ltd, listed on Shenzhen Stock Exchange (SZSE: 002161.SZ). Employing over 500 people globally, Invengo is one of the largest publicly traded, RFID oriented companies in the world.

#### **Features**


- Operating Frequency
   840 ~ 868 MHz and 902 ~ 928 MHz
- High Gain
- Circular Polarization
- Low VSWR
- Protection Level: IP65
- Durable and clean design
- Simple installation and maintenance



### **Radiation Pattern**

# 

#### E Phase



## **Product Specifications**

#### **Performance Parameter**

**Operating Frequency** 840 ~ 868 Mhz

902 ~ 928 MHz

 $\begin{tabular}{ll} VSWR & \leq 1.3:1 \\ Gain & 7.15 \ dBi \end{tabular}$ 

H-Plane HPBW  $60^{\circ}$ E-Plane HPBW  $60^{\circ}$ Polarization Circular
Antenna Impedance  $50 \Omega$ 

#### **Environmental**

**Operating Temperature**  $-40^{\circ}\text{C to }70^{\circ}\text{C }(-40^{\circ}\text{F to }158^{\circ}\text{F})$ 

 $\textbf{Storage Temperature} \qquad \quad -40^{\circ}\text{C to } 70^{\circ}\text{C } (-40^{\circ}\text{F to } 158^{\circ}\text{F})$ 

Humidity Range 5% -

Protection Level IP65

#### **Physical Parameters**

**Dimensions** 291 x 291 x 52 mm

11.5 x 11.5 x 2 in

5% ~ 95% RH


Weight Approx. 0,91 kg / 2.0 Lbs


Case Material Plastic ASA, Aluminium


#### **Models**

ID XC-AF12

# **Mounting Bracket**







#### **RFID Solutions**

www.rfidsolutionsinc.com

sales@rfidsolutionsinc.com

561 271 1727